

# TechNote – AltitudeCDN™ OmniCache Integration with PGI iMeetLive

Version 1.0

---

AltitudeCDN™ OmniCache is a robust enterprise video caching-proxy that enables the efficient delivery of HLS, DASH, and MP4 progressive-download behind the firewall. OmniCache provides a flexible, scalable, and distributed platform that delivers high-quality low-latency video, while conserving limited enterprise Wide Area Network (WAN) resources.

This guide describes how to configure a PGI iMeetLive video event leverage AltitudeCDN OmniCache.

## Contents

Contents .....	1
Introduction .....	2
Requirements .....	2
PGI iMeetLive OmniCache Configuration .....	2

# Introduction

AltitudeCDN OmniCache is a robust video proxy cache optimized to deliver enterprise video content with the lowest possible impact on your network infrastructure and security. AltitudeCDN OmniCache improves video playback performance by reducing latency and buffering, and minimizes the amount of bandwidth required for delivering rich media content across the WAN.

When used with iMeetLive, OmniCache is easily configurable as a software-defined network (SDN) reverse proxying solution that supports HLS, the primary streaming format used by iMeetLive, and MP4 progressive download. The OmniCache iMeetLive integration uses a PGI-provided portal player that re-writes video content URLs to steer traffic to an OmniCache node, allowing OmniCache to process and cache live or video on demand iMeetLive requests automatically.

# Requirements

To use OmniCache with iMeetLive, the following requirements exist:

Item	Recommendation
<b>OmniCache</b>	OmniCache v1.5.0 or later. For more requirement information, see the <i>AltitudeCDN OmniCache Deployment Guide</i> .
<b>Enterprise DNS</b>	Enterprise Domain Name System (DNS) configuration identifying the IP address of the internal OmniCache node. Geo-aware DNS may be employed to provide location-specific OmniCache routing. OmniCache routing may also be used to distribute load to alternate OmniCache nodes.

# PGI iMeetLive OmniCache Configuration

This section summarizes the configuration steps for using OmniCache with PGI iMeetLive (for more information on the iMeetLive interface, see PGI documentation):

1. Create a new Event.
2. Within Event Settings, set the appropriate values for the Event Name, Event Type, and Archive Events settings.

Player and Branding Options for Town Hall Video Event (1208336)

Player Settings

Media Options ⓘ  
Large Widescreen Video (480x270) ▾

Stream Type: HTML5 ⓘ

Multicast Type:  None  Ramp Multicast  Ramp Cache ⓘ

Slides ⓘ  
 Use PowerPoint Slides  
 Allow viewers to control slides

Audience Questions ⓘ  
 Allow during Live event  
 Send questions to these email addresses:   
Separate entries by semicolons. Example: chuck@example.com;steven@example.com  
 Allow during On-Demand event

Audience Phone Bridge ⓘ  
 Allow audience to listen to the presentation by phone

Player Layout Example:  
BANNER LOGOS  
VIDEO  
Q & A  
SLIDES

3. Within the Player and Branding Options:
  - For Media Options, select:
    - Stream Type: HTML5
    - Multicast Type: Ramp Cache
  - Set the appropriate values for the Slides, Audience Questions, and Audience Phone Bridge settings.
4. Within Event Summary > Ramp Cache Setup panel:

Ramp Setup

Stream Name	Stream ID	Ramp Server	Action
-------------	-----------	-------------	--------

Source :

Local url :  Omnicache server : For example , <https://ramp.webcasts.com>

Unicast Fallback

Enabled

- Select the source you want to cache with OmniCache: Prelive or Primary Stream.
- Set the Local URL of the enterprise local OmniCache (the hostname must be defined within the enterprise DNS to resolve to the address of the primary OmniCache). For example: `https://omnicache.customer.net:8443`
- Set Unicast Fallback to Enabled if you want user requests to fall back to the direct unicast stream from the Talkpoint source if OmniCache is unavailable.